


PURE 45


- Round floor recessed fixture.
- Recessed box and 0.50m cable supplied.
- 700mA converter to be ordered separately.
- Max. 11 PURE 45 by CD105.


This product contains 1 light source(s) of energy efficiency G.





CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
OU125	ALUMINIUM	DC 700mA 3V	3W	4000K	200 Lm	124 Lm


CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD172	2-4W	AC 230V	DC 700mA	1	1	85°	50°
CD105	9-35W	AC 230V	DC 700mA	1	1	65°	40°


 Recessed floor mounting only.


 Indoor and outdoor use.

 IP67 Dust-tight. Watertight (immersible).


 IK06 Protection against an impact energy of 1 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Hole cut to insert luminaire (36mm)


 Hole cut to insert recessed housing. (45mm).


 Beam 24°.


 Product in conformity CE.


 CRI >80 Colour rendering index >80.


 LED L70B50 50.000h LED specifications.


 RG1 Photobiological risk RG1

 650° Test on 650°.

 Power supply not included.

 Series connection.

 700 mA Connect to a constant current Led power supply of 700mA DC.

 3 3 years warranty.



 Non-replaceable light source.