


# RAY

- Spotlight for accent lighting.
- Adapter for Track UNO.
- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Non-dimmable or dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR41805	MATT BLACK	ALUMINIUM	AC 230V	13W	2700-3000-4000K	1405 Lm (4000K)	995 Lm (4000K)
TR41830	MATT WHITE	ALUMINIUM	AC 230V	13W	2700-3000-4000K	1405 Lm (4000K)	1015 Lm (4000K)
TR43005	MATT BLACK	ALUMINIUM	AC 230V	15W	2700-3000-4000K	1580 Lm (4000K)	1050 Lm (4000K)
TR43030	MATT WHITE	ALUMINIUM	AC 230V	15W	2700-3000-4000K	1580 Lm (4000K)	1050 Lm (4000K)



MATT BLACK

MATT WHITE



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 38°.



Product in conformity CE.



CRI>90



3 CCT.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.




Power supply included.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.