


# RAYPRO 50

- Spotlight for outdoor lighting.
- Black silk-screened glass diffuser.
- Supplied with 1.50m cable (HO5RN-F 3x0.75mm<sup>2</sup>).
- Non-dimmable converter built in the device.

This product contains 18 light source(s) of energy efficiency E.




CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
PRO50/M/3K/A	ANTHRACITE	CAST ALUMINIUM	AC 230V	50W	3000K	5400 Lm	4120 Lm
PRO50/M/3K/G	MATTE GREY	CAST ALUMINIUM	AC 230V	50W	3000K	5400 Lm	4120 Lm
PRO50/M/3K/W	MATT WHITE	CAST ALUMINIUM	AC 230V	50W	3000K	5400 Lm	4120 Lm



ANTHRACITE

MATTE GREY

MATT WHITE



Wall mounting only.



Outdoor use.



Dust-tight. Watertight (immersible).



Protection against an impact energy of 20 Joules.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 180°.



Horizontal orientation maximum to 355°.



Beam 36°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG0



Test on 650°.




Power supply included.



2 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Non-replaceable control gear.



Non-replaceable light source.