

RIESA

- Accent spotlight for outdoor lighting.

- 1.50 cable with stake to be buried included.
- Non-dimmable converter built in the device.

This product contains 4 light source(s) of energy efficiency G.





CODE		COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
OU461W	W24	ANTHRACITE	CAST ALUMINIUM	AC 230V	6W	3000K	550 Lm	398 Lm
ACCESS	OIRES	COLOR	DESCR	IPTION				
OU46224	1	ANTHRACITI	e shield					
OU48405	5		CONNEC	CTOR 2PIN IP68				
OU48505	5		CONNEC	CTOR 3PIN IP68				
) Wa	all mounti	ng only.						ŧ
Gr	round mou	unting only.						¥
	utdoor use	3.						•
65	Protected against the ingress of dust. Protected against jets of water.							
Protection against an impact energy of 2 Joules.								
	Earth wire . Fixture equipped with primary insulation only.							
Ve 120°	ertical orie	ntation maximum to	120°.					
355°		rientation maximum	to 355°.					
30° Be	eam 30°.							
	oduct in c	onformity CE.						
CRI >80	RI>80							
L70B50 50.000h	ED specific							
RG1		ical risk RG1						
650°	est on 650							
Po	ower supp	ly included.						
3 3 y	years warı	ranty.						

OUTDOOR

SPIKE LIGHTS



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.

Non-replaceable light source.

