


RONGA 1 RDX-B

- Adjustable round recessed spotlight.
- Fastened with slats.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- Decorative rings to be ordered separately.

This product contains 1 light source(s) of energy efficiency F (3000K), G (4000K).




CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO469WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 150mA 36V	7W	3000K	590 Lm	385 Lm
DO469WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 150mA 36V	7W	3000K	590 Lm	385 Lm
DO469NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 150mA 36V	7W	4000K	670 Lm	408 Lm
DO469NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 150mA 36V	7W	4000K	670 Lm	408 Lm



MATT BLACK



MATT WHITE

ACCESSOIRES	COLOR	DESCRIPTION
DO48025	SILVER	FRAME 
DO48060	GOLD	FRAME 



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (47mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 40°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 850°.





Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 150mA DC.




The product is dimmable.




3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.