


# RONGA 2 RDX-B

- Adjustable round recessed spotlight.
- Fastened with louvers.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- Decorative rings to be ordered separately.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO470WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 200mA 36V	9W	3000K	980 Lm	527 Lm
DO470WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 200mA 36V	9W	3000K	980 Lm	527 Lm
DO470NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 200mA 36V	9W	4000K	1070 Lm	793 Lm
DO470NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 200mA 36V	9W	4000K	1070 Lm	793 Lm



MATT BLACK



MATT WHITE

ACCESSOIRES	COLOR	DESCRIPTION
DO48125	SILVER	FRAME
DO48160	GOLD	FRAME



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (62mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 40°.



Product in conformity CE.



CRI >80



LED specifications.



Photobiological risk RG1



Test on 850°.





Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 200mA DC.




The product is dimmable.




3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.