


# RONGA 3 RDX-B

- Adjustable round recessed spotlight.
- Fastened with louvers.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.
- Decorative rings to be ordered separately.

This product contains 1 light source(s) of energy efficiency F.  
of energy efficiency E.

of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO471WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 270mA 36V	12W	3000K	1160 Lm	656 Lm
DO471WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 270mA 36V	12W	3000K	1160 Lm	656 Lm
DO471NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 270mA 36V	12W	4000K	1240 Lm	888 Lm
DO471NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 270mA 36V	12W	4000K	1240 Lm	888 Lm



MATT BLACK



MATT WHITE

ACCESSOIRES	COLOR	DESCRIPTION
DO48225	SILVER	FRAME
DO48260	GOLD	FRAME



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (62mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 40°.



Product in conformity CE.



CRI>80




LED specifications.



Photobiological risk RG1



Test on 850°.





Product can not be covered after installation even with insulation.



Class II power supply included.



Connect to a constant current Led power supply of 270mA DC.




The product is dimmable.




3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.