





















SIRA R


- 3 in 1 fixed round downlight.
- Exposed or semi-recessed mounting.
- 3000K, 4000K or 6000K as desired via a switch at the end of the luminaire.
- Fastened with adjustable springs to cover the recess diameters from 65 to 180mm.
- Non-dimmable converter built in the device.



This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO36630	MATT WHITE	COMPOSITE	AC 230V	18W	3000-4000-6000K	2150 Lm (4000K)	1599 Lm (4000K)

-  Recessed ceiling mounting only.
-  Ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.
-  Protection against an impact energy of 0,35 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Hole cut to insert luminaire (65mm to 180mm)
-  Beam 110°.
-  Product in conformity CE.
-  CRI>80
-  LED specifications.
-  3 CCT.
-  Photobiological risk RG0
-  Test on 650°.
-  Product can not be covered after installation even with insulation.
-  Power supply included.
-  3 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Non-replaceable light source.