

















SKIP 2

- Wall or ceiling lamp for outdoor lighting.
- Metallic reflector and polycarbonate optics.
- Translucent anti-glare film supplied.
- IP65 for wall mounting and IP44 for ceiling mounting.
- Non dimmable converter built in the device.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
OU28201	BLACK	CAST ALUMINIUM	AC 230V	30W	3000K	3800 Lm	3230 Lm
OU28203	METAL	CAST ALUMINIUM	AC 230V	30W	3000K	3800 Lm	3230 Lm
OU28204	WHITE	CAST ALUMINIUM	AC 230V	30W	3000K	3800 Lm	3230 Lm



-  Wall and ceiling mounting only.
-  Outdoor use.
-  Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.
-  Protected against the ingress of dust. Protected against jets of water.
-  Protection against an impact energy of 5 Joules.
-  Earth wire . Fixture equipped with primary insulation only.
-  Beam 120°.
-  Product in conformity CE.
-  CRI>85
-  LED specifications.
-  Photobiological risk RG1
-  Test on 850°.
-  Power supply included.
-  5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com

