


# SKIP

- Wall or ceiling lamp for outdoor lighting.
- Polycarbonate metal and optical reflector.
- Translucent anti-glare film supplied.
- IP65 in wall mounting and IP44 in ceiling mounting.
- Non-dimmable converter built in the device.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
OU28101	BLACK	CAST ALUMINIUM	AC 230V	12W	3000K	1800 Lm	1538 Lm
OU28103	METAL	CAST ALUMINIUM	AC 230V	12W	3000K	1800 Lm	1538 Lm
OU28104	WHITE	CAST ALUMINIUM	AC 230V	12W	3000K	1800 Lm	1538 Lm



BLACK



METAL



WHITE



Wall and ceiling mounting only.



Outdoor use.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 5 Joules.



Earth wire . Fixture equipped with primary insulation only.



Beam 120°.



Product in conformity CE.



CRI>85



LED specifications.



Photobiological risk RG1



Test on 850°.



Power supply included.



5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

