






# SOLIS 3

This product contains 1 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
P2C19S60WA	WHITE	ALUMINIUM	AC 230V	DC 1500mA	60W	4000K	8250 Lm	6600 Lm
P2C19X60WA	WHITE	ALUMINIUM		DC 1500mA	60W	4000K	8250 Lm	6600 Lm

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)
TR28000677			DRIVER 60W 900-1750mA CC DALI PUSH-DIM	220 
P2SMC	WHITE	ALUMINIUM	SURFACE MOUNTING KIT	1200 
P1SKC			SUSPENSION KIT	
LEDEP10			EMERGENCY CONVERTER	200 



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Beam 90°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



UGR below 19.



Photobiological risk RG0



Test on 650°.




Product can not be covered after installation even with insulation.




Connect to a constant current Led power supply of 1500mA DC.

**5** 5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.