




# SOLIS PRO CSP

This product contains 1 light source(s) of energy efficiency B.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	System Lumen
SOLP66N4K	WHITE	ALUMINIUM	AC 230V	DC 620mA	22W	4000K	3520 Lm
				DC 675mA	24W		3840 Lm
				DC 720mA	26W		4160 Lm
				DC 775mA	28W		4480 Lm

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)	
P2SMA	WHITE	ALUMINIUM	SURFACE MOUNTING KIT	600	
LEDEP10			EMERGENCY CONVERTER	200	



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,35 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Beam 90°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



UGR below 19.



Photobiological risk RG0



Test on 850°.




Product can not be covered after installation even with insulation.




Power supply included.



5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.