





















# SOLIS PRO


This product contains 1 light source(s) of energy efficiency B.




CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
SOLP66X4K	WHITE	ALUMINIUM	DC 775mA	28W	4000K	5400 Lm	4480 Lm

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)	
PS6501100MA			DRIVER 40W 650-1100mA CC DALI PUSH-DIM 0-10V	125	
P2SMA	WHITE	ALUMINIUM	SURFACE MOUNTING KIT	600	
LEDEP10			EMERGENCY CONVERTER	200	

-  Recessed ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.
-  Protection against an impact energy of 0,35 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Beam 90°.
-  Product in conformity CE.
-  Colour rendering index >80.
-  LED specifications.
-  UGR below 19.
-  Photobiological risk RG0
-  Test on 850°.
-  Product can not be covered after installation even with insulation.
-  Power supply not included.
-  Connect to a constant current Led power supply of 775mA DC.
-  5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.