


SORA POWER

- Adjustable rectangular recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converters supplied (dali versions: converters with push-dim funcgton).



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
PHASE CUT DIMMABLE									
DO409SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x784 Lm	15°
DO409SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x784 Lm	15°
DO409WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x941 Lm	15°
DO409WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x941 Lm	15°
DO409NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x993 Lm	15°
DO409NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x993 Lm	15°
DO408SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x688 Lm	30°
DO408SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x688 Lm	30°
DO408WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x862 Lm	30°
DO408WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x862 Lm	30°
DO408NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x887 Lm	30°
DO408NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x887 Lm	30°
DO407SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x807 Lm	50°
DO407SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x807 Lm	50°
DO407WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x996 Lm	50°
DO407WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x996 Lm	50°
DO407NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x1010 Lm	50°
DO407NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x1010 Lm	50°
DALI DIMMABLE									
DO409SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x784 Lm	15°
DO409SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x784 Lm	15°
DO409WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x941 Lm	15°
DO409WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x941 Lm	15°
DO409NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x993 Lm	15°
DO409NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x993 Lm	15°
DO408SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x688 Lm	30°
DO408SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x688 Lm	30°
DO408WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x862 Lm	30°
DO408WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x862 Lm	30°
DO408NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x887 Lm	30°
DO408NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x887 Lm	30°

CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
DALI DIMMABLE									
DO407SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x807 Lm	50°
DO407SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	2700K	2x1260 Lm	2x807 Lm	50°
DO407WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x996 Lm	50°
DO407WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	3000K	2x1300 Lm	2x996 Lm	50°
DO407NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x1010 Lm	50°
DO407NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	2xDC 350mA 36V	2x13W	4000K	2x1340 Lm	2x1010 Lm	50°



MATT BLACK

MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Rectangular piercing to insert the luminaire. (192x102mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Horizontal orientation maximum to 355°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.



Connect to a constant current Led power supply of 350mA DC.



The product is dimmable.



5 years warranty.



Photometric data available on our website: www.indigo-lighting.com