


SPIRA 3 RX

- Adjustable round recessed spotlight.
- Protective glass.
- Fastened with springs.
- Remote non dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO344NW04	WHITE	CAST ALUMINIUM	AC 230V	DC 1500mA 37V	60W	4000K	8680 Lm	7124 Lm



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (215mm)



Minimum ceiling height to insert luminaire. (240mm)



Vertical orientation maximum to 80°.



Horizontal orientation maximum to 350°.



Beam 40°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.




Connect to a constant current Led power supply of 1500mA DC.




3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.