


SPOTI R-B

- Fixed round recessed spotlight.
- Fastened with slats.
- Pre-wired 1.50m.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Remote non dimmable converter supplied, can be placed 10m maximum from the device.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO241SW25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	2700K	480 Lm	416 Lm
DO241SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	2700K	480 Lm	416 Lm
DO241SW38	ANODIZED ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	2700K	480 Lm	341 Lm
DO241WW25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	3000K	480 Lm	445 Lm
DO241WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	3000K	480 Lm	445 Lm
DO241WW38	ANODIZED ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	3000K	480 Lm	365 Lm
DO241NW25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	4000K	490 Lm	450 Lm
DO241NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	4000K	490 Lm	450 Lm
DO241NW38	ANODIZED ANTHRACITE	CAST ALUMINIUM	AC 230V	DC 500mA 9V	4,5W	4000K	490 Lm	375 Lm



ALUMINIUM



MATT WHITE



ANODIZED ANTHRACITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,50 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (35mm)



Beam 24°.



Product in conformity CE.



CRI>80



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Class II power supply included.




Connect to a constant current Led power supply of 500mA DC.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.