






SPRINGBOK LITE 1


- High bay hanging fixture.
- Tempered glass diffuser.
- 1.50m black H05RN-F power cable and M10 suspension loop included.
- Non dimmable converter built in the device.
- Can be installed at heights of up to 15m.
- Optional accessories :
270° adjustable mounting bracket, 80° prismatic reflector, microwave detector and remote control for setting the parameters of the detector(s).
- Default microwave detector settings : hold time 5 sec., daylight sensor disable, detection range 100%.





Remote control is required to configure other settings.
This product contains a light source(s) of energy class D.


CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
HB100WW05	BLACK	CAST ALUMINIUM	AC 230V	80W	3000K	12350 Lm	8715 Lm
HB100NW05	BLACK	CAST ALUMINIUM	AC 230V	80W	4000K	13150 Lm	9865 Lm


ACCESSOIRES	COLOR	DESCRIPTION	
HB105		80° PC PRISMATIC REFLECTOR 309x160mm	
HB104	BLACK	270° ADJUSTABLE MOUNTING BRACKET	
HB103	BLACK	IP65 MICROWAVE DETECTOR KIT	
HB115		REMOTE CONTROL FOR MW DETECTOR	

 Suspended mounting only.


 Indoor use only.


 Protected against the ingress of dust. Protected against jets of water.


 Protection against an impact energy of 2 Joules.


 Earth wire . Fixture equipped with primary insulation only.


 Beam 110°.


 Product in conformity CE.

 Colour rendering index >80.


 LED specifications.


 Photobiological risk RG1


 Test on 850°.

 Power supply included.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Non-replaceable light source.