LED STRIPS & PROFILES LED STRIPS



L (mm)

ST125

- RGB+W LED strip.
- 5m roll.
- Prewired at start and end of strip.
- Sticker.

CODE

- Breakable every 6 LEDs, 25 mm.
- Converter, controller and accessories to be ordered separately.

DC



		-	_	
				2
				2

LED Lumen

ST125RGBW	DC 24V	19,2W/m	RGB+W (6000K)	320 Lm/m (6000K)	5000
ACCESSOIRES	COLOR	DESCRIPTION			
ST126	WHITE	CONNECTOR RGBW			
ST127	WHITE	INTERCONNECTOR RGBW			
ST128	WHITE	CONNECTOR L RGBW			1000 1000 1000 1000 1000 1000 1000 100
ST129	WHITE	CONNECTOR T RGBW			1200 a 12
ST130	WHITE	CONNECTOR X RGBW			2000 2000 2000 2000 2000 2000 2000 200

T° (K)

LED

Indoor use only.

IP 33

Protected against the ingress of solid bodies greater than 2,5mm. Protected against rain.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Product in conformity CE.



RGB + White.

RG1

Photobiological risk RG1

Power supply not included.

24V DC

Connect to a constant voltage LED power supply of 24VDC.

3 years warranty.