


ST135

- Waterproof LED strip.
- 5m roller. Pre-wired at the beginning of the strip.
- Breakable every 50mm (only 3000K and 4000K) and every 83 mm (RGB).
- Converter, controller and accessories to be ordered separately.
- Accessories compatible only with ST135WW and ST135NW, except profiles and end.



CODE	DC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
ST135WW	DC 24V	9,6W/m	3000K	520 Lm/m	479 Lm/m	5000
ST135NW	DC 24V	9,6W/m	4000K	550 Lm/m	509 Lm/m	5000
ST135RGB	DC 24V	12W/m	RGB	-	-	5000

ACCESSOIRES	DESCRIPTION	
ST136	CONNECTOR CABLE END	
ST137	CONNECTOR CABLE BOTTOM	
ST138	CONNECTOR CABLE LEFT SIDE	
ST139	CONNECTOR CABLE RIGHT SIDE	
ST140	INTERCONNECTOR	
ST141	INTERCONNECTOR WITH 30cm CABLE	
ST142	FLEXIBLE PROFILE L:0,5m 2 PC	
ST143	PC PROFILE L:1m	
ST144	ALUMINIUM PROFILE L:1m	
ST145	END CAP	

Indoor and outdoor use.

IP 67 Dust-tight. Watertight (immersible).

Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

Product in conformity CE.



CRI>80



Photobiological risk RG1



Power supply not included.



Connect to a constant voltage LED power supply of 24VDC.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com