


# STEPBEAM






- Decorative wall recessed fixture for corridor lighting.
- Round or square magnetic front to be ordered separately.
- Fastened with blades.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.



CODE	MATERIAL	AC	LED	T° (K)	LED Lumen
STEPBEAM30	ALUMINIUM	AC 230V	2,7W	3000K	255 Lm

ACCESSOIRES	COLOR	DESCRIPTION	
RBEZCIRCLEB	BLACK	STEPBEAM ROUND FRONT CIRCULAR DIFFUSION	
RBEZCIRCLES	SATIN CHROME	STEPBEAM ROUND FRONT CIRCULAR DIFFUSION	
RBEZCIRCLEW	WHITE	STEPBEAM ROUND FRONT CIRCULAR DIFFUSION	
RBEZHIRCLEB	BLACK	STEPBEAM ROUND FRONT SEMI-CIRCULAR DIFFUSION	
RBEZHIRCLES	SATIN CHROME	STEPBEAM ROUND FRONT SEMI-CIRCULAR DIFFUSION	
RBEZHIRCLEW	WHITE	STEPBEAM ROUND FRONT SEMI-CIRCULAR DIFFUSION	
RBEZSLOTB	BLACK	STEPBEAM ROUND FRONT LINEAR DIFFUSION	
RBEZSLOTWS	SATIN CHROME	STEPBEAM ROUND FRONT LINEAR DIFFUSION	
RBEZSLOTW	WHITE	STEPBEAM ROUND FRONT LINEAR DIFFUSION	
SBEZCIRCLEB	BLACK	STEPBEAM SQUARE FRONT CIRCULAR DIFFUSION	
SBEZCIRCLES	SATIN CHROME	STEPBEAM SQUARE FRONT CIRCULAR DIFFUSION	
SBEZCIRCLEW	WHITE	STEPBEAM SQUARE FRONT CIRCULAR DIFFUSION	
SBEZHIRCLEB	BLACK	STEPBEAM SQUARE FRONT SEMI-CIRCULAR DIFFUSION	

ACCESSOIRES	COLOR	DESCRIPTION	
<b>SBEZHRCIRCLES</b>	SATIN CHROME	STEPBEAM SQUARE FRONT SEMI-CIRCULAR DIFFUSION	
<b>SBEZHRCIRCLEW</b>	WHITE	STEPBEAM SQUARE FRONT SEMI-CIRCULAR DIFFUSION	
<b>SBEZSLOTB</b>	BLACK	STEPBEAM SQUARE FRONT LINEAR DIFFUSION	
<b>SBEZSLOTWS</b>	SATIN CHROME	STEPBEAM SQUARE FRONT LINEAR DIFFUSION	
<b>SBEZSLOTW</b>	WHITE	STEPBEAM SQUARE FRONT LINEAR DIFFUSION	



Recessed wall mounting only.



Indoor use only.



Protected against dust, And protected against water spray.



Protection against an impact energy of 0,50 Joule.



Earth wire . Fixture equipped with primary insulation only.



Hole cut to insert luminaire (45 mm)



Product in conformity CE.



Colour rendering index >90.



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.




The product is dimmable.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.