


SULLY C

- Linear wall lamp.
- Polycarbonate difusser.
- Supplied with black or white power cable.
- DALI dimmable converter included in the profile.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA178WW05	MATT BLACK	ALUMINIUM	AC 230V	26W	3000K	3500 Lm	2850 Lm
WA178WW30	MATT WHITE	ALUMINIUM	AC 230V	26W	3000K	3500 Lm	2850 Lm
WA178NW05	MATT BLACK	ALUMINIUM	AC 230V	26W	4000K	3700 Lm	3000 Lm
WA178NW30	MATT WHITE	ALUMINIUM	AC 230V	26W	4000K	3700 Lm	3000 Lm




MATT BLACK





MATT WHITE


ACCESSOIRES	DESCRIPTION	L (mm)
CD127	DALI PCU LIGHTING MANAGEMENT	48




 Ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 0,20 Joule.


 Earth wire . Fixture equipped with primary insulation only.


 Beam 105°.


 Product in conformity CE.


 CRI>80

 LED specifications.


 Photobiological risk RG1

 Test on 650°.

 Power supply included.

 The product is dimmable (DALI input).

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com