


# SUNY 1

- Portable luminaire.
- 2700K or 3000K as desired via a switch.
- 2 modes, automatic (works only if luminosity <30 lux) or manual.
- With switch and battery rechargeable via USB plug or via solar cells.
- Charging time 6 hours (USB), 20 hours (solar) with a battery life of 20 hours (50%), 9 hours (100% intensity).
- Supplied with USB cable, without charger.
- Dimmable.



This product contains 50 light source(s) of energy efficiency G.

CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
OU45424	ANTHRACITE	ALUMINIUM	DC 3,7V	2,2W	2700-3000K	210 Lm (3000K)	120 Lm (3000K)
OU45447	CORTEN STEEL	ALUMINIUM	DC 3,7V	2,2W	2700-3000K	210 Lm (3000K)	120 Lm (3000K)



ANTHRACITE



CORTEN STEEL

ACCESSOIRES	COLOR	DESCRIPTION
OU45524	ANTHRACITE	WALL HOOK
OU45547	CORTEN STEEL	WALL HOOK



Mobile.



Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Product in conformity CE.



CRI >80



2 CCT.



LED specifications.



Photobiological risk RG1



Test on 650°.



With solar cells.




Rechargeable battery via USB plug.



With dimmer switch.



3 years warranty.



Replaceable LED light source by an electrician.