


SWING RD



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO332WW05	MATT BLACK	COMPOSITE	AC 230V	DC 120mA 54V	8W	3000K	850 Lm	580 Lm
DO332WW30	MATT WHITE	COMPOSITE	AC 230V	DC 120mA 54V	8W	3000K	850 Lm	645 Lm
DO332NW05	MATT BLACK	COMPOSITE	AC 230V	DC 120mA 54V	8W	4000K	900 Lm	615 Lm
DO332NW30	MATT WHITE	COMPOSITE	AC 230V	DC 120mA 54V	8W	4000K	900 Lm	685 Lm



NOIR MAT



BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against dust, And protected against water spray.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



Beam 60°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply included.




Connect to a constant current Led power supply of 120mA DC.





The product is dimmable.



5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.