


SYLA RD-B

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with louvers.
- Remote dimmable converter supplied.
- As an option, DALI CD123 dimmable converter to be ordered separately.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO221SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	2700K	960 Lm	776 Lm
DO221SW18	BLACK - GOLD	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	2700K	960 Lm	776 Lm
DO221SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	2700K	960 Lm	776 Lm
DO221WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	3000K	1010 Lm	851 Lm
DO221WW18	BLACK - GOLD	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	3000K	1010 Lm	851 Lm
DO221WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 250mA 37V	10W	3000K	1010 Lm	851 Lm







MATT BLACK



BLACK - GOLD



MATT WHITE

ACCESSOIRES	COLOR	DESCRIPTION	
DO33905	MATT BLACK	SYLA R-B SQUARE RING 100x100mm	 75
DO33930	MATT WHITE	SYLA R-B SQUARE RING 100x100mm	 75
DO34005	MATT BLACK	SYLA R-B RECTANGULAR RING 195x100mm	 183x93
DO34030	MATT WHITE	SYLA R-B RECTANGULAR RING 195x100mm	 183x93

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD123	3-18W	AC 230V	DC 250mA	1	1	80°C	50°C



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.




Hole cut to insert luminaire (75mm)





Beam 38°.





 Product in conformity CE.


 CRI>90


 LED specifications.


 Photobiological risk RG1


 Test on 650°.


 Product can not be covered after installation even with insulation.


 Power supply included.


 Connect to a constant current Led power supply of 250mA DC.

 The product is dimmable.

 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.