


THEA LITE CSP 2

This product contains 1 light source(s) of energy efficiency B.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
THL2N	WHITE	ALUMINIUM	AC 230V	DC 350mA	14W	3000-4000-6500K	2000 Lm (4000K)	1680 Lm (4000K)
THL2X	WHITE	ALUMINIUM		DC 350mA	14W	3000-4000-6500K	2000 Lm (4000K)	1680 Lm (4000K)

ACCESSOIRES	DESCRIPTION	L (mm)
PS250600MA	DRIVER 13-29W 250-600mA CC DALI PUSH-DIM 0-10V	125
LEDEP10	EMERGENCY CONVERTER	200



Recessed ceiling mounting only.

Indoor use only.

Protected against dust, And protected against water spray.

Protection against an impact energy of 0,35 Joule.

Live parts are equipped with additional isolation protection, such as reinforced or double insulation.

Hole cut to insert luminaire (150 mm)

Beam 90°.

Product in conformity CE.

Colour rendering index >80.

Selectable colour temperature.

LED specifications.

UGR below 25.


Test on 850°.

Product can not be covered after installation even with insulation.


Connect to a constant current Led power supply of 350mA DC.

5 years warranty.





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.