


THEA PRO 1

This product contains 1 light source(s) of energy efficiency B.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
THP1N	WHITE	ALUMINIUM	AC 230V	DC 200mA	10W	4000K	1600 Lm	1400 Lm
THP2N	WHITE	ALUMINIUM	AC 230V	DC 350mA	14W	4000K	2400 Lm	2000 Lm
THP1X	WHITE	ALUMINIUM		DC 200mA	10W	4000K	1600 Lm	1400 Lm
THP2X	WHITE	ALUMINIUM		DC 350mA	14W	4000K	2400 Lm	2000 Lm

ACCESSOIRES	DESCRIPTION	L (mm)	
THP1DD	DRIVER DALI PUSH-DIM THP1		
THP23DD	DRIVER DALI PUSH-DIM THP2 / THP3		
THP12UGR	REFLECTOR UGR<19 THP1 / THP2		
LEDEP10	EMERGENCY CONVERTER	200	



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (145mm to 180mm)



Beam 80°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



UGR below 22.



Test on 850°.




Product can not be covered after installation even with insulation.




5 years warranty.





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.