


THEA PRO 2

This product contains 1 light source(s) of energy efficiency B.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
THP3N	WHITE	ALUMINIUM	AC 230V	DC 350mA	14W	4000K	2400 Lm	2000 Lm
THP4N	WHITE	ALUMINIUM	AC 230V	DC 650mA	25W	4000K	4400 Lm	3500 Lm
THP3X	WHITE	ALUMINIUM		DC 350mA	14W	4000K	2400 Lm	2000 Lm
THP4X	WHITE	ALUMINIUM		DC 650mA	25W	4000K	4400 Lm	3500 Lm

ACCESSOIRES	DESCRIPTION	L (mm)	
THP23DD	DRIVER DALI PUSH-DIM THP2 / THP3		
THP4DD	DRIVER DALI PUSH-DIM THP4		
THP34UGR	REFLECTOR UGR<19 THP3 / THP4		
LEDEP10	EMERGENCY CONVERTER	200	



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (165mm to 200mm)



Beam 80°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



UGR below 22.



Test on 850°.



Product can not be covered after installation even with insulation.



5 years warranty.





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.