

## TIGA 1 RD



- 3 in 1 fixed round recessed downlight.
- 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Dimmable converter integrated in the device.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO35630	MATT WHITE	COMPOSITE	AC 230V	12W	3000-4000-6000K	1600 l m (4000K)	985 Lm (4000K)

Recessed ceiling mounting only.

Indoor use only.

Protected against the ingress of solid bodies greater than 1mm. Protected against splashing

**IK** Protection against an impact energy of 0,35 Joule.

Live parts are equipped with additional isolation protection, such as reinforced or double insulation.

Hole cut to insert luminaire. (155mm) 155

Beam 100°.

Product in conformity CE. CE

CRI>80 CRI

100°

LED LED specifications.

Photobiological risk RG0

RG0

3000 K 4000 K 6000 K 3 CCT.

Test on 650°. 650°

Product can not be covered after installation even with insulation.

Power supply included.

The product is dimmable.

3 years warranty.

@

Photometric data available on our website: www.indigo-lighting.com

Replaceable control gear by an electrician.

Non-replaceable light source.