


# TIGA 2 RD



- 3 in 1 fixed round recessed downlight.
- 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Dimmable converter built in the device.
- Compatible with end-of-phase dimmer.



This product contains 1 light source(s) of energy efficiency G.

| CODE    | COLOR      | MATERIAL  | AC      | LED | T° (K)          | LED Lumen       | System Lumen    |
|---------|------------|-----------|---------|-----|-----------------|-----------------|-----------------|
| DO35730 | MATT WHITE | COMPOSITE | AC 230V | 18W | 3000-4000-6000K | 2350 Lm (4000K) | 1622 Lm (4000K) |



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,35 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (205mm)



Beam 100°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG0



3 CCT.



Test on 650°.



Product can not be covered after installation even with insulation.



Power supply included.




The product is dimmable.




3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Non-replaceable light source.