## **DOWNLIGHTS**



## TIGA 3 RD



- 3 in 1 fixed round recessed downlight.
- 3000K, 4000K or 6000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Dimmable converter built in the device.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO35830	MATT WHITE	COMPOSITE	AC 230V	24W	3000-4000-6000K	2870 Lm (4000K)	2083 Lm (4000K)

L	JU3583U	MATT WHITE	COMPOSITE	AC 230V	24W	3000-4000-6000K	2870 Lm (4000K)	2083 Lm (4000K)
	Recessed	d ceiling mounting only.						
	Indoor us	e only.						
	Protected water.	I against the ingress of s	olid bodies greater tha	n 1mm. Protected aga	inst splashing			

**IK** Protection against an impact energy of 0,35 Joule.

Live parts are equipped with additional isolation protection, such as reinforced or double insulation.

Hole cut to insert luminaire (225mm) 225

Beam 100°. 100°

Product in conformity CE. CE

CRI LED LED specifications.

CRI>80

Photobiological risk RG0 RG0 3 CCT.

3000 K 4000 K 6000 K Test on 650°. 650°

Product can not be covered after installation even with insulation.

Power supply included. The product is dimmable.

3 years warranty.

Photometric data available on our website: www.indigo-lighting.com @

Replaceable control gear by an electrician. Non-replaceable light source.