


TINY R

- Round floor recessed fixture.
- Opaline diffuser.
- White (4000K) or blue (BL) LED.
- Carrossable résistance 650kg.
- Recessed box and 1.00m cable supplied.
- 350mA converter to be ordered separately.
- Max. 14 TINY by CD114.



This product contains 1 light source(s) of energy efficiency G.

CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
OU16816	STAINLESS STEEL 316	DC 350mA 3V	1W	4000K	150 Lm	80 Lm
OU26116	STAINLESS STEEL 316	DC 350mA 3V	1W	BL	-	-

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD114	2-18W	AC 230V	DC 350mA	1	1	70°	50°



Recessed floor mounting only.



Indoor and outdoor use.



Dust-tight. Watertight (immersible).



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire. (20mm)



Hole cut to insert recessed housing. (21mm).



Beam 120°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply not included.



Series connection.



Connect to a constant current Led power supply of 350mA DC.



Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.



3 years warranty.





Non-replaceable light source.