


TIPI RX

- Adjustable round recessed spotlight.
- Fastened with springs.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Remote non dimmable converter supplied, can be placed at 10m maximum from the device.



This product contains 1 light source(s) of energy efficiency F.

CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO104WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 9V	3W	3000K	350 Lm	300 Lm
DO104WW25	ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 350mA 9V	3W	3000K	350 Lm	300 Lm
DO104WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 9V	3W	3000K	350 Lm	300 Lm



MATT BLACK



ALUMINIUM



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (55 mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 30°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Class II power supply included.



Connect to a constant current Led power supply of 350mA DC.




5 years warranty.




Photometric data available on our website: www.indigo-lighting.com





Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.