


TOMY 1 C



- Linear ceiling lamp.
- Low luminance reflector.
- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Supplied with black or white power cable.
- Non-dimmable converter built in the device.



















This product contains 66 light source(s) of energy efficiency F.


CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA22405	MATT BLACK	ALUMINIUM	AC 230V	36W	2700-3000-4000K	4100 Lm (4000K)	2835 Lm (4000K)
WA22430	MATT WHITE	ALUMINIUM	AC 230V	36W	2700-3000-4000K	4100 Lm (4000K)	2835 Lm (4000K)



MATT BLACK

MATT WHITE

-  Ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Beam 36°.
-  Product in conformity CE.
-  CRI >80
-  3 CCT.
2700K
3000K
4000K
-  LED specifications.
L70B50
50.000h
-  UGR below 19.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com

 Non-replaceable control gear.



Non-replaceable light source.