
**INDOOR** 



# **TRACK 48VDC SURFACE**

- 48 VDC exposed track.
- Converter to be ordered separately.
- The converter may be remote or included in the track using a box provided for that purpose (TR25005 + CD144 or TR37505).
  Max 20m and 400W in a continuous line.





CODE	COLOR	MATERIAL	DC	L (mm)
TR24005	MATT BLACK	ALUMINIUM	DC 48V MAX 9,5A	1000
TR24105	MATT BLACK	ALUMINIUM	DC 48V MAX 9,5A	2000
TR24205	MATT BLACK	ALUMINIUM	DC 48V MAX 9,5A	3000

ACCESSOIRES	COLOR	DESCRIPTION						
DRIVERS								
ΓR24605	MATT BLACK	LIVE END + CABLE 150cm	24 75					
CONNECTORS								
ΓR24805	METAL	MECHANICAL CONNECTION	S S S S S S S S S S S S S S S S S S S					
FR24705	MATT BLACK	LIVE END W/O CABLE	[24 75					
TR24305	MATT BLACK	CONNECTOR L 90° CEILING WITH TR24805	74 74 54					
TR24405	MATT BLACK	CONNECTOR L 90° CEILING IN WITH TR24805	99 99					
TR24505	MATT BLACK	CONNECTOR L 90° CEILING OUT WITH TR24805	99. 99					
TR24905	MATT BLACK	LIVE END + CABLE FOR TR243/244/245 TR263/264/265	24: 124					
ΓR36505	MATT BLACK	LIVE L 90° CONNECTOR INSIDE CEILING	54					
ΓR36605	MATT BLACK	LIVE LEFT T CONNECTOR CEILING	54 70					
TR36705	MATT BLACK	LIVE RIGHT T CONNECTOR CEILING	54 70					
TR36805	MATT BLACK	LIVE X CONNECTOR CEILING	54 110 110					
TR37205	MATT BLACK	LIVE DUAL CONNECTOR 120° CEILING	54 110					
ΓR37305	MATT BLACK	LIVE TRIPLE CONNECTOR 120° CEILING	54 128					

#### **INDOOR**





FRACKS 8	SPOTLIGHTS	ARCHITECTURAL		LIGHTING
CCESSOIRES	COLOR	DESCRIPTION		
		CONNECTORS		
R37405	MATT BLACK	HEXAGON SHAPE CONNECTOR CEILING	128	
		DRIVERS		
R25005	MATT BLACK	BOX + CABLE 150cm FOR DRIVER 90W	280	
R37505	MATT BLACK	DRIVER 225W 48V WITH BOX	543	
D144		DRIVER 90W 48V	205 225 20	
D145		DRIVER 180W 48V	244 71 38	
D146		DRIVER 400W 48V	240 125	
		DIMMABLE DRIVERS		
CD165		DRIVER 65W 48V DALI-PUSH	235 100	
:D166		DRIVER 135W 48V DALI-PUSH	235	
		SUSPENSION ACCESSORY		
R25105	MATT BLACK	HANGING STEEL WIRE 150cm	1500	
		MOLDING		
R25205	MATT BLACK	COVER 100cm	1000	
R25305	MATT BLACK	COVER 200cm	2000	
R25405	MATT BLACK	COVER 300cm	3000	
		FINISHING TIP		
R25505	MATT BLACK	END CAP	54	
Wall and	I ceiling mounting only.		VIIIIII	
Suspend Indoor us	led mounting only.		r F	
Protected	d against the ingress of s	solid bodies greater 12 mm. No protection against the ingress	J	
Product	can be connected to low	voltage systems. A safety extra low voltage luminaire in of SELV are not generated.		

# TECHNICAL DATA

## **INDOOR**

## TRACKS & SPOTLIGHTS ARCHITECTURAL



Product in conformity CE.

Power supply not included.

48V Connect to a constant voltage LED power supply of 48VDC.

3 years warranty.