




























TRACK III SURFACE















- Exposed track.
- Mains voltage 220/250V.
The three-phase connection allows a total current of 16A on each circuit. BR> This corresponds to 3 x 3680VA = 11040VA.
- A track can support a load of 6kg/0.20m with a maximum distance of 1.00m between fixing points or a load of 3kg/0.20m with a maximum distance of 2.00m between fixing points.





CODE	COLOR	MATERIAL	AC	Watt Max	L (mm)
TR22030	BLACK	ALUMINIUM	AC (3x) 230V 16A	(3x) 3680VA	1000
TR22031	WHITE	ALUMINIUM	AC (3x) 230V 16A	(3x) 3680VA	1000
TR22130	BLACK	ALUMINIUM	AC (3x) 230V 16A	(3x) 3680VA	2000
TR22131	WHITE	ALUMINIUM	AC (3x) 230V 16A	(3x) 3680VA	2000
TR22230	BLACK	ALUMINIUM	AC (3x) 230V 16A	(3x) 3680VA	3000
TR22231	WHITE	ALUMINIUM	AC (3x) 230V 16A	(3x) 3680VA	3000


ACCESSOIRES	COLOR	DESCRIPTION	L (mm)
TR22330	BLACK	POWER CONNECTOR RIGHT	
TR22331	WHITE	POWER CONNECTOR RIGHT	
TR22430	BLACK	POWER CONNECTOR LEFT	
TR22431	WHITE	POWER CONNECTOR LEFT	
TR22530	BLACK	CENTRAL POWER CONNECTOR	
TR22531	WHITE	CENTRAL POWER CONNECTOR	
TR22630	BLACK	CONNECTOR ELECTRICAL	
TR22631	WHITE	CONNECTOR ELECTRICAL	
TR22730	BLACK	MECHANICAL CONNECTION	
TR22731	WHITE	MECHANICAL CONNECTION	


ACCESSOIRES	COLOR	DESCRIPTION	L (mm)
TR22830	BLACK	CONNECTION L90° INSIDE	
TR22831	WHITE	CONNECTION L90° INSIDE	
TR22930	BLACK	CONNECTION L90° OUTSIDE	
TR22931	WHITE	CONNECTION L90° OUTSIDE	
TR23030	BLACK	CONNECTION X	
TR23031	WHITE	CONNECTION X	
TR23130	BLACK	CONNECTION T RIGHT	
TR23131	WHITE	CONNECTION T RIGHT	
TR23230	BLACK	CONNECTION T LEFT	
TR23231	WHITE	CONNECTION T LEFT	
TR36030	BLACK	FLEXIBLE CONNECTOR	
TR36031	WHITE	FLEXIBLE CONNECTOR	
TR23330	BLACK	ADAPTER MECHANICAL	
TR23331	WHITE	ADAPTER MECHANICAL	
TR23430	BLACK	ADAPTER 10A MAX 5KG	
TR23431	WHITE	ADAPTER 10A MAX 5KG	

ACCESSOIRES	COLOR	DESCRIPTION	L (mm)	
TR24030	BLACK	SUSPENSION HOOK		
TR24031	WHITE	SUSPENSION HOOK		
TR23530	BLACK	KIT CEILING MOUNT		
TR23531	WHITE	KIT CEILING MOUNT		
TR23630	BLACK	KIT SUSPENSION L:500cm		
TR23631	WHITE	KIT SUSPENSION L:500cm		
TR23930	BLACK	SUPPORTING PIECE L:18cm	180	
TR23931	WHITE	SUPPORTING PIECE L:18cm	180	
TR23730	BLACK	ENDCAP		
TR23731	WHITE	ENDCAP		
TR23830	BLACK	FINISHING MOULDING L:300cm	3000	
TR23831	WHITE	FINISHING MOULDING L:300cm	3000	
TR24130	BLACK	SURFACE MOUNTED BASE		
TR24131	WHITE	SURFACE MOUNTED BASE		

 Ceiling mounting only.

 Suspended mounting only.

 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Earth wire . Fixture equipped with primary insulation only.



Product in conformity CE.



Test on 650°.



2 years warranty.