






























TRACK UNO












- Exposed track.
- Mains voltage 220/250V.
The single-phase connection allows a total current of 16A, which corresponds to 380VA. .
- The track can support a load of 10g maximum between two fixing points.
- The TR411 reinforcement piece can be fitted to the TR412 suspension kit.





CODE	COLOR	MATERIAL	AC	Watt Max	L (mm)
TR40105	BLACK	ALUMINIUM	AC 230V 16A	3680VA	2000
TR40104	WHITE	ALUMINIUM	AC 230V 16A	3680VA	2000
TR40205	BLACK	ALUMINIUM	AC 230V 16A	3680VA	3000
TR40204	WHITE	ALUMINIUM	AC 230V 16A	3680VA	3000


ACCESSOIRES	COLOR	DESCRIPTION	L (mm)
TR40305	BLACK	POWER CONNECTOR RIGHT	
TR40304	WHITE	POWER CONNECTOR RIGHT	
TR40405	BLACK	POWER CONNECTOR LEFT	
TR40404	WHITE	POWER CONNECTOR LEFT	
TR40505	BLACK	CENTRAL POWER CONNECTOR	
TR40504	WHITE	CENTRAL POWER CONNECTOR	
TR40605	BLACK	ELECTRICAL CONNECTION	
TR40604	WHITE	ELECTRICAL CONNECTION	
TR40705	BLACK	CONNECTION L90° INSIDE	
TR40704	WHITE	CONNECTION L90° INSIDE	
TR40805	BLACK	CONNECTION L90° OUTSIDE	


ACCESSOIRES	COLOR	DESCRIPTION	L (mm)
TR40804	WHITE	CONNECTION L90° OUTSIDE	
TR40905	BLACK	CONNECTION 20-180° INSIDE	
TR40904	WHITE	CONNECTION 20-180° INSIDE	
TR42105	BLACK	CONNECTION 20-180° OUTSIDE	
TR42104	WHITE	CONNECTION 20-180° OUTSIDE	
TR44105	BLACK	CONNECTION T INSIDE RIGHT	
TR44104	WHITE	CONNECTION T INSIDE RIGHT	
TR44005	BLACK	CONNECTION T OUTSIDE RIGHT	
TR44004	WHITE	CONNECTION T OUTSIDE RIGHT	
TR44305	BLACK	CONNECTION T INSIDE LEFT	
TR44304	WHITE	CONNECTION T INSIDE LEFT	
TR44205	BLACK	CONNECTION T OUTSIDE LEFT	
TR44204	WHITE	CONNECTION T OUTSIDE LEFT	
TR44405	BLACK	CONNECTION X	
TR44404	WHITE	CONNECTION X	
TR41005	BLACK	6A ADAPTER WITH M10 THREADED TUBE MAX 5KG	
TR41004	WHITE	6A ADAPTER WITH M10 THREADED TUBE MAX 5KG	


ACCESSOIRES	COLOR	DESCRIPTION	L (mm)	
TR41120	ALUMINIUM	SUPPORT PIECE L:8cm		
TR41105	BLACK	SUPPORT PIECE L:8cm		
TR41104	WHITE	SUPPORT PIECE L:8cm		
TR41205	BLACK	SUSPENSION KIT L:150cm		
TR41204	WHITE	SUSPENSION KIT L:150cm		
TR41305	BLACK	ENDCAP		
TR41304	WHITE	ENDCAP		
TR41405	BLACK	FINISHING MOULDING L:200cm	2000	
TR41404	WHITE	FINISHING MOULDING L:200cm	2000	
TR41505	BLACK	FINISHING MOULDING L:300cm	3000	
TR41504	WHITE	FINISHING MOULDING L:300cm	3000	


 Ceiling mounting only.


 Suspended mounting only.

 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

 Earth wire . Fixture equipped with primary insulation only.

 Product in conformity CE.

 3 years warranty.