


# VIGO

- Luminaire for accent lighting for 48V track.
- Low luminance reflector.




This product contains 1 light source(s) of energy efficiency F.


This product contains 1 light source(s) of energy efficiency F.


This product contains 1 light source(s) of energy efficiency F.


This product contains 1 light source(s) of energy efficiency F.


CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α
<b>NOT DIMMABLE</b>								
TR272WW05	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	888 Lm	12°
TR272NW05	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	1015 Lm	12°
TR271WW05	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	915 Lm	24°
TR271NW05	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	995 Lm	24°
TR270WW05	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	939 Lm	36°
TR270NW05	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	984 Lm	36°
<b>DALI DIMMABLE</b>								
TR272WW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	888 Lm	12°
TR272NW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	1015 Lm	12°
TR271WW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	915 Lm	24°
TR271NW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	995 Lm	24°
TR270WW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	3000K	1030 Lm	939 Lm	36°
TR270NW05DA	MATT BLACK	ALUMINIUM	DC 48V	12W	4000K	1270 Lm	984 Lm	36°


 Wall and ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 0,20 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Vertical orientation maximum to 90°.


 Product in conformity CE.


 CRI>80


 LED specifications.

 UGR below 19.

 Photobiological risk RG1


 Test on 650°.

 Connect to a constant voltage LED power supply of 48VDC.

 3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.