


# WL94

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WL9410SCS	WHITE	POLYCARBONATE	AC 230V	10W	3000-4000-6500K	1300 Lm (4000K)	1100 Lm (4000K)
WL9418SCS	WHITE	POLYCARBONATE	AC 230V	18W	3000-4000-6500K	2350 Lm (4000K)	2000 Lm (4000K)
WL9410MCS	WHITE	POLYCARBONATE	AC 230V	10W	3000-4000-6500K	1300 Lm (4000K)	1100 Lm (4000K)
WL9418MCS	WHITE	POLYCARBONATE	AC 230V	18W	3000-4000-6500K	2350 Lm (4000K)	2000 Lm (4000K)
WL9410ECS	WHITE	POLYCARBONATE	AC 230V	10W	3000-4000-6500K	1300 Lm (4000K)	1100 Lm (4000K)
WL9410CCS	WHITE	POLYCARBONATE	AC 230V	10W	3000-4000-6500K	1300 Lm (4000K)	1100 Lm (4000K)
WL9418CCS	WHITE	POLYCARBONATE	AC 230V	18W	3000-4000-6500K	2350 Lm (4000K)	2000 Lm (4000K)



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 2 Joules.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Beam 120°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.




LED specifications.




Power supply included.



3 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.